

Signtac® Self-Adhesive Floor Graphics

A professional range of certified, fire and slip-rated floor-graphic products to suit a variety of indoor and outdoor applications. No minimum order quantity.



Range overview (see table opposite for full details and comparison):

Signtac® 6 Indoor (PVC)

- Short term (up to 6 months durability), indoor only.
- Specifically developed for simple tool-free installation.
- Clean and quick removal within 6 months.

Signtac® 6 Indoor (PET)

- Short term (up to 6 month durability), PVC free, indoor only.
- Easy to apply and dimensionally stable.
- Repositionable whilst installing.

Signtac® 12 Indoor

- 2-part laminated for longer term (up to 12 months), indoor only.
- Removable, non-damaging adhesive.
- Ideal for mid to heavy foot traffic areas.

Signtac® 12 Outdoor SS

- 2-part laminated for longer term (up to 12 months), outdoor or indoor.
- Aggressive adhesive suitable for low-energy surfaces and ideal for smooth concrete outdoors.

Signtac® 12 Outdoor RS

- Longer term (up to 12 months), outdoor.
- For coarse textured surfaces such as brick, concrete, asphalt, etc.
- Easy to apply, does not shrink and 100% recyclable.



Standard shapes and sizes:

Circles – 100mm, 200mm and 300mm dia.

Square – 100mm, 200mm and 300mm sq.

Triangles – 100mm, 200mm and 300mm sides.

Non-standard shapes and sizes:

Cut to shape within standard poster sizes A4, A3, A2, A1 and A0 and within 100/200/300mm squares.

Note – for optimum adhesion and safety, sharp corners and intricate cut detail in designs should be avoided.

		Indoor			Indoor & Outdoor	
		One Part	One Part	Two Part (laminated)	Two Part (laminated)	One Part
Product		Sigtac® 6 Indoor (PVC)	Sigtac® 6 Indoor (PET)	Sigtac® 12 Indoor	Sigtac® 12 Outdoor SS	Sigtac® 12 Outdoor RS
Description		200mic monomeric PVC film	170mic PET film	Vinyl: 90mic white monomeric PVC Laminate: 100mic matt pebble textured monomeric PVC	Vinyl: 80mic white polymeric PVC Laminate: 100mic matt pebble textured monomeric PVC	250mic white aluminium film
		Fire and slip-rated floor graphics for public spaces	Fire and slip-rated PVC-free floor graphic material	Slip-rated combination designed for floor graphic use on a variety of surfaces	Fire and slip-rated combination designed for floor graphic use on a variety of smooth outdoor surfaces	Fire and slip-rated floor graphic engineered for coarse textured outdoor floor surfaces
Applications		Indoor carpets (low pile), indoor tiles, indoor hardwood, sealed concrete, sealed wood, waxed vinyl, marble, terrazzo			Indoor/outdoor smooth concrete, brick and marble.	Outdoor tarmac, stone, ceramic tiles, paving slabs, indoor/outdoor concrete, brick
Adhesive		Removable	Removable	Removable	Permanent	Permanent
Slip Ratings	Pendulum Test Method	Low slip potential 40 PTV	Low slip potential 38 PTV	Low slip potential 36 PTV	Low slip potential 36 PTV	Low slip potential 72 PTV
	Ramp Test	R10	R10	R11	R11	R12
Fire Ratings		B1	Bfl – s1	Fire ratings not available	Combined Bfl – s1	Bfl – s1
Durability Dependent upon proper installation and foot traffic.		Short term up to 6 months indoor	Short term up to 6 months indoor	Long term up to 12 months indoor	Long term up to 12 months outdoor	Long term up to 12 months outdoor